REMARKS

### 1.   Statement Regarding Substitute Specification

Enclosed herewith is a Substitute Specification based upon the PCT application from which the present application is a U.S. national filing. Also enclosed is a marked up copy of the PCT specification showing the changes made. The Substitute Specification includes no new matter.

2.   Claim Amendments

After amendment to claims 1-5 and addition of newly presented claims 6-10, claims 1-10 are presented for examination herein.

Respectfully submitted,

December 23, 2004

Carol W. Burton, Reg. No. 35,465
HOGAN & HARTSON
One Tabor Center
1200 17th Street, Suite 1500
Denver, Colorado 80202
(303) 454-2454 Tel
(303) 899-7333 Fax

[["]]System for driving rows of a liquid crystal display[[."]]

5

[[* * * *]]

~~DESCRIPTION~~

1.   Field of the Invention.

The present invention refers to a system for driving rows of a liquid crystal display.

10   2.   Background of the Invention.

Liquid crystal displays (LCD) are used today in an ever-increasing number of products such as cellular telephone<u>s</u>, portable computers, etc. The displays, <u>which</u> [[that]] can be in black and white, <u>or</u> in a grey or <u>colors</u> ~~colours~~ scale, are usually made up of a matrix of electrodes in rows and columns ~~which, appropriately~~ driven by

15   <u>the </u>application of a<u>n</u> <u>appropriate</u> voltage signal, ~~cause at the crossing points, the so-called pixels,~~ a change in <u>the</u> optic <u>behavior</u> ~~behaviour~~ of the liquid crystal placed between[[.]] <u>them occurs at the crossing points ("the pixels")</u>.

The image that is visualized on the display is obtained through different possible methods for driving the rows and the columns.

20   One method that is often used for driving an LCD and known as Improved Alt & Pleshko (IA&P) requires a single row electrode to be excited for an elementary period of time by [[means]] [[of]] a single spurt tone and the simultaneous excitation of the column electrodes; to the latter are then applied voltage values suitable for determining the powering up or the powering down of all the pixels that belong to that

25   single row. For a successive period of elementary time there <u>is</u> a<u>n</u> [[will]] [[be]] the excitation of another row electrode and so on until the scanning of the last row electrode is completed; therefore if the row electrodes are a number N and T is the period of elementary time, the time needed for scanning all the rows <u>is</u> [[will]] [[be]] given by NT which is also called <u>a</u> "frame".

The optic transmission characteristics of the liquid crystal vary with the amplitude of the voltage applied to the relative pixel, but the application of direct voltage is damaging for the liquid crystal as it permanently changes and degrades the physical properties of the material. For this reason the voltage signals used to drive

5   the single pixels of an LCD are alternating voltage signals in relation to a common value of direct voltage that not necessarily has to be [[the]] ground potential. In this manner the driving of a pixel of the display comes about through two waveforms of equal amplitude but with opposite polarity in relation to a common voltage, which [[that]] follow each other periodically. Therefore the driving voltage applied to a

10   given pixel during its period T within a frame is applied with opposite polarity during the respective period T of the successive frame.

Nevertheless all these voltage transitions involve a significant power that has to be managed by the drive circuits. Therefore one of the primary purposes in planning the driving devices of LCD rows and columns is to reduce the power consumption so

15   as to minimize minimise both the power delivered by the power supplies of said devices, and the power dissipated by them.

One part of a driving device of LCD rows and columns, more precisely the Philips PCF8548 device, is described in Figure 1.

The LOW_FRAME signal is a logic signal that equals zero [[0]] in the even

20   frames, and equals one [[1]] in the uneven frames. ROW_ON instead is a logic signal that equals zero [[0]] when the row in question is not selected, equalling one [[1]] when it is being scanned. Starting from these two signals, through a circuit 1, the control signals that drive two PMOS transistors [[PMOS]] T9, T10 and two NMOS transistors [[NMOS]] T7, T8 are generated. In particular the gate terminals of the

25   transistors T8, T9 are T10 are driven through three [[3]] identical circuit cells C1, shown in Figure 2. Said cells are level-shifters, that is, buffers that convert the logic signal levels from low voltage to high voltage, in particular, from the supply voltage VDD to a driving voltage VLCD generated by a device (not shown in the Figure) comprising a booster regulator through the connection of a certain number of stages

30   of a charge pump.

Each cell C1 comprises two NMOS transistors [[NMOS]] M22 and M23 driven by [[the]] signals A and NA, the output signal of the logic circuitry 1 and the negative signal A. The source terminals of the transistors M22 and M23 are connected to the voltage VSS and the drain terminals are connected respectively to the drain terminals of two PMOS transistors [[PMOS]] M20 and M21 on the source terminal of which the voltage VLCD is present; in addition, the drain terminals of [[the]] transistors M22 and M23 are connected to the gate terminals of the transistors M21 and M20. The outputs Q drive the gate of [[the]] transistors T10, T9 and T8.

The gate terminal of [[the]] transistor T7 is instead driven directly by a logic low voltage signal.

The source terminal of [[the]] transistor T9 is connected to a voltage reference VA while the drain terminal is connected to the drain terminal of [[the]] transistor T10 whose source terminal is connected to the voltage VLCD. The source terminal of [[the]] transistor T8 is connected to a voltage reference VB while the drain terminal is connected to the drain terminal of [[the]] transistor T7 whose source terminal is connected to the voltage VSS. The drain terminals of the pairs of transistor T7-T8 and T9-T10 are in common and supply the output signal OUT.

The voltages VA and VB are different levels of intermediate voltages between the voltages VLCD and VSS that are generated inside the drive device of an LCD. The ratio between these levels and VLCD is chosen on the basis of the dimension of the matrix of the display according to the criteria that is [[will]] [[be]] shown below.

In particular, according to the technique of Improved Alt & Pleshko, to drive the liquid crystal display adequately, four different levels of intermediate voltage between VLCD and VSS are generated inside the device. The relation between these voltages and VLCD is set on the basis of the number of rows m of the display according to the relations:

$$VLCD, [(n+3)/(n+4)]*VLCD, [(n+2)/(n+4)]*VLCD, [2/(n+4)]*VLCD,$$
$$[1/(n+4)]*VLCD, VSS)$$

with $n = \sqrt{m}$ ~~3 given at the square root of m-3.~~

If, for example, m = 81 => n = 6 in the case of a display with 81 rows the voltage levels will be:

VLCD   (9/10)*VLCD   (8/10)*VLCD   (2/10)*VLCD   (1/10)*VLCD

VSS.

With reference to the drive circuit of Figure 1, in the case of a drive of rows, the voltage references VA and VB [[will]] [[be]] equal respectively to (9/10)*VLCD and (1/10)*VLCD. The drive <u>operates</u> ~~will come about, for example,~~ in the following manner: in a frame [[the]] transistors T9 and T7 <u>are</u> [[will]] [[be]] turned on alternately while <u>transistors</u> T10 and T8 <u>are</u> [[will]] [[be]] off; in this case the output signal OUT, suitable for driving a row, <u>varies</u> [[will]] [[vary]] between VSS and VA according to whether the row is being scanned or not. In the successive frame, [[the]] transistors T10 and T8 <u>are</u> [[will]] [[be]] turned on alternately while [[the]] transistors T9 and T7 <u>are</u> [[will]] [[be]] off and therefore the output signal will vary between VLCD and VB according to whether the row is being scanned or not. The waveforms of the output signal OUT in the case of driving two rows ROW0 and ROW1 for a frame n and for the successive frame n+1 are shown in Figure 3. The Figure 4 shows the image as it appears on the display.

SUMMARY OF THE INVENTION

<u>According to an embodiment of</u> ~~In view of the state of the technique, the object of~~ the present invention [[is]] [[to]] ~~produce~~ a system for driving rows of a liquid crystal display [[that]] has a minor number of components in comparison to [[the]] known system<u>s</u> and therefore occupies a smaller overall area in the integration of the system.

In accordance with <u>an embodiment of</u> the present invention, ~~this object is achieved by means of~~ a system for driving rows of a liquid crystal display <u>include</u> ~~characterised in that it comprises~~ at least one module for driving a single row of said liquid crystal display, said module <u>including</u> ~~comprising~~ an inverter operating in a supply path between a first and a second supply line of said system, said first supply line <u>including</u> ~~comprising~~ first means capable of connecting it to a first or to a second supply voltage and said second supply line <u>including</u> ~~comprising~~ second means

capable of connecting it to a third or to a fourth supply voltage, said inverter being driven by a logic circuitry and sending in output a driving signal for a single row of said liquid crystal display.

BRIEF DESCRIPTION OF THE DRAWINGS

5   The characteristics and the advantages of the present invention are [[will]] appear evident from the following detailed description of an embodiment thereof illustrated as non-limiting example in the enclosed drawings, in which:

Figure 1 is a circuitry diagram of a row driving device of an LCD according to the known art;

10   Figure 2 is a more detailed circuitry diagram of a part of the circuit of Figure 1;

Figure 3 shows waveforms of the output voltage signal of the circuit of Figure 1 in the case of driving two rows;

Figure 4 shows an image formed on the display of an LCD;

Figure 5 is a circuitry diagram of a system for driving the rows of an LCD

15   according to an embodiment of the invention;

Figure 6 shows the time waveforms LOW_FRAME, ROW_ON and OUT of the device of Figure 5.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

With reference to [[the]] Figure 5 a circuit diagram of a system for driving rows

20   of an LCD according to the present invention is shown. Said system uses various drive modules 10, [[every]] one for each row of the display[[,]] [[e]] Each module [[of]] [[which]] comprises [[a]] low voltage logic circuitry 11 coupled to a level-shifter device 12 that drives a PMOS transistor [[PMOS]] T11 and a NMOS transistor [[NMOS]] T12 forming an inverter and having a single output terminal OUT where

25   the signal for driving a single row is present. [[The]] [[t]] Transistors T11 and T12 are coupled to two supply lines 21 and 22 that can be connected to two different supply voltages, respectively VLCD, VA and VB, VSS, through two selector switches S1 and S2 controlled by a signal F_x which is a function of the signal LOW_FRAME. Said

signal F [[will]] causes the switching of [[the]] switch S1 on VA and of [[the]] switch S2 on VSS if the signal LOW_FRAME is at logic level zero [[0]], while it [[will]] causes the commutation of [[the]] switch S1 on VLCD and of [[the]] switch S2 on VB if the signal LOW_FRAME is at the logic level one [[1]].

5   [[The]] [[c]] Circuitry 11, which is preferably made up of only one XOR gate [[XOR]], operates in a supply path between the supply voltages VDD and VSS and in input has the two logic signals LOW_FRAME and ROW_ON, in which the logic signal LOW_FRAME is a logic signal that is equal to zero [[0]] in the even frames, and is equal to one [[1]] in the uneven frames while the logic signal ROW_ON is

10   equal to zero [[0]] when the row in question is not selected, and is equal to one [[1]] when being scanned.

       The output signal A has the value of [[the]] voltages VDD and VSS and together with the signal NA, that is the negative signal A, drives the elevator device or level-shifter 12 that operates between the supply voltages VLCD and VSS and has a

15   similar circuit structure to the cell C1 of Figure 2. The output signal Q of the device 12 drives the gate of the two transistors T11 and T12.

       If in an even generic frame n (the signal LOW_FRAME=0), if the row selected is being scanned (the signal ROW_ON=1), the output signal of the device 12 has [[will]] [[have]] the value of the voltage VLCD and the output signal OUT has [[will]]

20   [[have]] the value of the voltage VSS. If instead the row selected is not being scanned (the signal ROW_ON=0), the output signal of the device 12 has [[will]] [[have]] the value of the voltage VSS and the output signal OUT has [[will]] [[have]] the value of the voltage VA.

       At the successive frame n+1 (the signal LOW_FRAME=1), if the row selected

25   is being scanned (the signal ROW_ON=1), the output signal of the device 12 has [[will]] [[have]] the value of the voltage VSS and the output signal OUT has [[will]] [[have]] the value of the voltage VLCD. If instead the row selected is not being scanned (the signal ROW_ON=0), the output signal of the device 12 has [[will]] [[have]] the value of the voltage VLCD and the output signal OUT has [[will]]

30   [[have]] the value of the voltage VB.

In the Figure 6 the time waveforms of the signals LOW_FRAME, ROW_ON and OUT are shown in two successive frames, that is for an even frame and for an uneven frame.

~~"System for driving rows of a liquid crystal display."~~

[[* * * *]]

ABSTRACT

The present invention describes a system for driving rows of a liquid crystal

5   display ~~comprising~~ including at least one module [[(10)]] for driving one single row

of the liquid crystal display. The module ~~comprises~~ includes an inverter ~~(T11 T12)~~

operating in a supply path between a first [[(21)]] and a second [[(22)]] supply line of

the system, where the first supply line [[(21)]] ~~comprises first means (S1) capable of~~

~~connecting it~~ includes a first switch for coupling the inverter to a first ~~(VLCD)~~ or to a

10   second [[(VA)]] supply voltage and the second supply line [[(22)]] ~~comprises second~~

~~means (S2) capable of connecting it~~ includes a second switch for coupling the inverter

to a third [[(VB)]] or to a fourth [[(VSS)]] supply voltage. The inverter ~~(T11 T12)~~ is

driven by [[a]] logic circuitry ~~(11 12)~~ and ~~sends in output (OUT)~~ provides a drive

signal for one single row of the liquid crystal display. ~~(Fig. 5)~~.